

<div><div><div></div><div>REFERENCE TO ELEVATION NUMBER REFERENCE TO SHEET NUMBER</div></div><div><div></div><div>REFERENCE TO DETAIL NUMBER REFERENCE TO SHEET NUMBER</div></div><div><div></div><div>REFERENCE TO SECTION NUMBER REFERENCE TO SHEET NUMBER</div></div><div><div></div><div>COLUMN GRID LINE DESIGNATION</div></div><div><div></div><div>PARTITION TYPE</div></div><div><div></div><div>DOOR NUMBER (SEE DOOR SCHED.)</div></div><div><div></div><div>INTERIOR ELEVATIONS</div></div><div><div></div><div>ROOM NAME AND NUMBER</div></div><div><div></div><div>ROOM NUMBER CEILING HEIGHT (SEE CEILING PLANS)</div></div><div><div></div><div>EXISTING WALL CONSTRUCTION TO REMAIN</div></div><div><div></div><div>EXISTING WALL CONSTRUCTION TO BE REMOVED</div></div><div><div></div><div>NEW DRYWALL PARTITION</div></div><div><div></div><div>NEW MASONRY PARTITION</div></div><div><div></div><div>EXISTING DOOR AND/OR FRAME TO BE REMOVED</div></div><div><div></div><div>EXISTING DOOR AND FRAME TO REMAIN</div></div><div><div></div><div>NEW DOOR AND FRAME IN GYPSUM BOARD WALL</div></div><div><div></div><div>NEW DOOR AND FRAME IN MASONRY WALL</div></div><div><div></div><div>EXISTING WALL TO BE PATCHED</div></div><div><div></div><div>SURFACE MOUNTED FIRE EXTINGUISHER (10 LBS, TYPE SUITABLE FOR FIRE TYPE)</div></div><div><div></div><div>WINDOW TYPE</div></div><div><div></div><div>FINISH TAG</div></div><div><div></div><div>ELEVATION TAG ELEV. 0'-0"</div></div><div><div></div><div>REVISION TAG</div></div></div>		<div><div><div>AIR CONDITIONING</div><div>ACOUSTICAL</div><div>ACCESS</div><div>ACOUSTICAL PANEL</div><div>ACOUSTICAL TILE</div><div>ADDENDUM</div><div>ADJACENT</div><div>ABOVE FINISH FLOOR</div><div>ALTERNATE</div><div>ALUMINUM</div><div>ARCHITECT (URAL)</div><div>ABOVE RAISED FLOOR</div><div>BOARD</div><div>BUILDING</div><div>BLOCK</div><div>BOTTOM OF</div><div>BEARING</div><div>BRICK</div><div>BASEMENT</div><div>BUILT UP ROOFING</div><div>CABINET</div><div>CATCH BASIN</div><div>CABLE HOLE IN CEILING</div><div>CABLE HOLE IN FLOOR</div><div>CEMENT</div><div>CLOSED CIRCUIT T.V.</div><div>CAST IRON</div><div>CENTER LINE</div><div>CEILING</div><div>CLOSET</div><div>CLEAR (ANCE)</div><div>CONCRETE MASONRY UNIT</div><div>COUNTER</div><div>COLUMN</div><div>CONCRETE</div><div>CONSTRUCTION</div><div>CONTRACT (OR)</div><div>CORRIDOR</div><div>CARPET</div><div>CERAMIC TILE</div><div>CENTER</div><div>DEMOLITION</div><div>DEPARTMENT</div><div>DRINKING FOUNTAIN</div><div>DIAMETER</div><div>DIAGONAL</div><div>DIMENSION</div><div>DIVISION</div><div>DEAD LOAD</div><div>DOWN</div><div>DAMP PROOFING</div><div>DOOR</div><div>DOWNSPOUT</div><div>DETAIL</div><div>DRAWING</div><div>DRAWER</div><div>EAST</div><div>EACH</div><div>EXHAUST FAN</div><div>ELECTRIC (AL)</div><div>ELEVATION</div><div>EMERGENCY</div><div>ENCLOSE (ENCLOSURE)</div><div>EXPANDED POLYSTYRENE</div><div>EQUAL</div><div>EACH WAY</div><div>ELECTRIC WATER COOLER</div><div>EXCAVATE</div><div>EXHAUST</div><div>EXISTING</div><div>EXPANSION JOINT</div><div>EXTERIOR</div><div>FLOOR DRAIN</div><div>FOUNDATION</div><div>FIRE EXTINGUISHER</div><div>FINISH (ED)</div><div>FIXTURE</div><div>FLOOR (ING)</div><div>FIREPROOF</div><div>FIREPROOF SELF-CLOSING</div><div>FEET</div><div>FOOTING</div><div>GAGE, GAUGE</div><div>GALVANIZED</div><div>GENERAL CONTRACT (OR)</div><div>GROUND FAULTINTERRUPT GLASS,</div><div>GLAZING</div><div>GYPSUM BOARD WALL</div><div>HOLLOW CORE</div><div>HEADER</div><div>HARDWARE</div><div>HEIGHT</div><div>HOLLOW METAL</div><div>HIGH POINT</div><div>HEATING</div><div>HEATING VENTILATION &amp;</div><div>AIR CONDITIONING</div><div>INSULATED CONCRETE FORM</div><div>ISOLATED GROUND</div><div>INCH</div><div>INSULATION (D) (ION)</div></div><div><div>A/C</div><div>AC</div><div>ACC</div><div>ACP</div><div>ACT</div><div>ADD</div><div>ADJ</div><div>AFF</div><div>ALT</div><div>ALUM</div><div>ARCH</div><div>ARF</div><div>BD</div><div>BLDG</div><div>BLK</div><div>BO</div><div>BRG</div><div>BRK</div><div>BSMT</div><div>BUR</div><div>CAB</div><div>CB</div><div>CBIC</div><div>CBIF</div><div>CEM</div><div>CCTV</div><div>CI</div><div>CL</div><div>CLG</div><div>CLO</div><div>CLR</div><div>CMU</div><div>CNTR</div><div>COL</div><div>CONC</div><div>CONST</div><div>CONTR</div><div>CORR</div><div>CPT</div><div>CT</div><div>CTR</div><div>DEMO</div><div>DEPT</div><div>DF</div><div>DIA</div><div>DIAG</div><div>DIM</div><div>DIV</div><div>DL</div><div>DN</div><div>DP</div><div>DR</div><div>DS</div><div>DTL</div><div>DWG</div><div>DWR</div><div>E</div><div>EA</div><div>EF</div><div>ELEC</div><div>ELEV</div><div>EMERG</div><div>ENCL</div><div>EPS</div><div>EQ</div><div>EW</div><div>EWC</div><div>EXC</div><div>EXH</div><div>EXIST</div><div>EJ</div><div>EXT</div><div>FD</div><div>FDN</div><div>FE</div><div>FIN</div><div>FIXT</div><div>FLR</div><div>FP</div><div>FPSC</div><div>FT</div><div>FTG</div><div>GA</div><div>GALV</div><div>GC</div><div>GFI</div><div>GL</div><div>GWB</div><div>HC</div><div>HDR</div><div>HDW</div><div>HGT</div><div>HM</div><div>HP</div><div>HTG</div><div>HVAC</div><div>ICF</div><div>IG</div><div>IN</div><div>INSUL</div></div><div><div>JANITOR'S CLOSET</div><div>LAMINATE (D)</div><div>LAVATORY</div><div>LIVELOAD</div><div>LOW POINT</div><div>MAXIMUM</div><div>MATERIAL</div><div>MECHANICAL</div><div>MANUFACTURE (R) (D)</div><div>MINIMUM</div><div>MIRROR</div><div>MASONRY OPENING</div><div>METAL</div><div>NORTH</div><div>NOT IN CONTRACT</div><div>NUMBER</div><div>NOMINAL</div><div>NOT TO SCALE</div><div>OVERALL</div><div>ON CENTER</div><div>OVERHEAD OR OPPOSITE HAND</div><div>OPENING</div><div>OPPOSITE</div><div>POURED CONCRETE</div><div>PLATE</div><div>PLASTIC</div><div>LAMINATE</div><div>PANEL</div><div>PARTITION</div><div>POLYVINYL CHLORIDE</div><div>RISER</div><div>RAISED ACCESS</div><div>RADIUS</div><div>REFLECTED CEILING PLAN</div><div>ROOF DRAIN</div><div>RTU ROOF TOP UNIT</div><div>REFERENCE</div><div>REFRIGERATOR</div><div>REINFORCED</div><div>RESILIENT</div><div>ROOFING</div><div>ROOM</div><div>ROUGH OPENING</div><div>SOUTH</div><div>SPLASH BLOCK</div><div>SOLID CORE WOOD DOOR</div><div>STORM DRAIN</div><div>SECTION</div><div>SQUARE FOOT</div><div>SIMILAR</div><div>STRUCTURAL INSULATED PANEL</div><div>SPECIFICATION(S)</div><div>SPRINKLER</div><div>SQUARE</div><div>SECONDARY ROOF DRAIN</div><div>STANDARD</div><div>STEEL</div><div>STORAGE</div><div>SUSPENDED</div><div>TREAD</div><div>TELEPHONE</div><div>THICK(NESS)</div><div>T.O.S. (TOP OF STEEL)</div><div>TOP OF TYPICAL</div><div>UNLESS OTHERWISE NOTED</div><div>VINYL COMPOSITE TILE</div><div>VIDEO DISPLAY TERMINAL</div><div>VERIFY IN FIELD</div><div>VINYL WALL COVERING</div><div>WEST</div><div>WITH</div><div>WALL BASE</div><div>WATER CLOSET</div><div>WOOD</div><div>WIRE MESH</div><div>WITHOUT</div><div>WATERPROOFING</div><div>WELDED WIRE MESH</div><div>WELDED WIRE FABRIC</div></div><div><div>JC</div><div>LAM</div><div>LAV</div><div>LL</div><div>LP</div><div>MAX</div><div>MATL</div><div>MECH</div><div>MFR (D)</div><div>MIN</div><div>MIR</div><div>MO</div><div>MTL</div><div>N</div><div>NIC</div><div>NO</div><div>NOM</div><div>NTS</div><div>OA</div><div>OC</div><div>OH</div><div>OPNG</div><div>OPP</div><div>PC</div><div>PL</div><div>PL</div><div>LAM</div><div>PNL</div><div>PTN</div><div>PVC</div><div>R</div><div>RA</div><div>RAD</div><div>RCP</div><div>RD</div><div>RO</div><div>REF</div><div>REFG</div><div>REINF</div><div>RES</div><div>RFG</div><div>RM</div><div>RO</div><div>S</div><div>SB</div><div>SCW</div><div>SD</div><div>SECT</div><div>SF</div><div>SIM</div><div>SIP</div><div>SPEC(S)</div><div>SPR</div><div>SQ</div><div>SRD</div><div>STD</div><div>STL</div><div>STOR</div><div>SUSP</div><div>T</div><div>TEL</div><div>THK</div><div>TO</div><div>TYP</div><div>UON</div><div>VCT</div><div>VDT</div><div>VIF</div><div>VWC</div><div>W</div><div>W/</div><div>WB</div><div>WC</div><div>WD</div><div>WM</div><div>W/O</div><div>WP</div><div>WWW</div><div>WWF</div></div></div>	<div><div><div>1. ALL WORK SHALL BE DONE IN STRICT ACCORDANCE WITH PROVISIONS OF LOCAL, STATE, AND FEDERAL, LAWS, ORDINANCES, AND REGULATIONS WHEREVER APPLICABLE. NOTIFY DESIGNATED REPRESENTATIVE OF ANY WORK FOUND NOT TO BE IN COMPLIANCE PRIOR TO COMMENCEMENT OF WORK.</div><div>2. EACH CONTRACTOR SHALL BECOME FAMILIAR WITH THE SCOPE OF WORK AND SHALL BE HELD TO HAVE VISITED THE SITE AND TO HAVE VERIFIED ALL EXISTING CONDITIONS PRIOR TO SUBMISSION OF BID.</div><div>3. IN ALL CASES, DRAWINGS SHALL NOT BE SCALED FOR INFORMATION. FIGURED DIMENSIONS AND CONDITIONS MUST BE VERIFIED IN THE FIELD.</div><div>4. CONTRACTOR SHALL VERIFY AND BE RESPONSIBLE FOR ALL FIELD DIMENSIONS AND JOB CONDITIONS, AND SHALL NOTIFY THE DESIGNATED REPRESENTATIVE OF ANY DISCREPANCIES, CONFLICTS, AND/OR OMISSIONS WHICH WOULD INTERFERE WITH THE SATISFACTORY COMPLETION OF THE WORK. SHOULD HE FAIL TO FOLLOW THIS PROCEDURE AND CONTINUE WITH THE WORK, HE SHALL ASSUME ALL RESPONSIBILITY AND LIABILITY ARISING THEREFROM. ALL DIMENSIONS ARE SHOWN TO FACE OF FINISHES UNLESS OTHERWISE NOTED.</div><div>5. ALL ITEMS OF WORK IDENTIFIED ON THE DRAWINGS BY NAME, NOTE, OR MATERIAL DESIGNATION ARE NEW, UNLESS OTHERWISE NOTED.</div><div>6. ALL NEW MATERIALS AND INSTALLATIONS SHALL BE IN ACCORDANCE WITH THE MANUFACTURERS LATEST PRINTED SPECIFICATIONS, AND WITH ALL APPLICABLE CODE REQUIREMENTS.</div><div>7. ALL WORK SHALL BE PERFORMED IN ACCORDANCE WITH BEST STANDARD TRADE PRACTICES. EACH TRADE SHALL COOPERATE WITH OTHER TRADES TO FACILITATE JOB SCHEDULING AND COMPLETION.</div><div>8. PROPRIETARY NAMES IDENTIFY SPECIFIC PRODUCTS OR ITEMS THAT ARE TO BE PROVIDED. NO SUBSTITUTIONS ARE PERMITTED UNLESS AUTHORIZED IN WRITING BY THE DESIGNATED REPRESENTATIVE.</div><div>9. GC IS RESPONSIBLE FOR PROTECTING WORK AREAS AND MATERIALS FROM THEFT, VANDALISM, AND OTHER LOSSES.</div><div>10. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR ANY DAMAGE TO ADJOINING REMAINING AREAS AS A RESULT OF HIS WORK, AND SHALL REPAIR DAMAGED SURFACES TO THEIR PRE-EXISTING CONDITIONS OR AS MAY BE REQUIRED TO COMPLETE THE ENTIRE SCOPE OF THE WORK.</div><div>11. GC IS RESPONSIBLE FOR PROTECTING ALL FINISHED SURFACES FROM UNWANTED PAINT, DIRT, OR OTHER DELETERIOUS MATERIALS.</div><div>12. ALTERATIONS TO EXISTING WORK SHALL BE PATCHED AND FINISHED, AS NECESSARY, TO MATCH EXISTING CONTIGUOUS SURFACES OR NEW FINISHES SHOWN.</div><div>13. AT THE COMPLETION OF EACH WORKDAY, EACH TRADE SHALL BE RESPONSIBLE FOR CLEANING UP THEIR WORK. RUBBISH REMOVAL SHALL BE DONE IN A DUST INHIBITIVE FASHION, AND THE JOB SITE SHALL BE FREE OF ALL DEBRIS AND BROOM CLEAN UPON COMPLETION.</div><div>14. CLEAN ALL FLOORS, WALLS, DOORS, FIXTURES, LIGHTS, MISCELLANEOUS GLASS, ETC. LEAVING JOB FREE OF DUST AND DEBRIS, PRIOR TO PROJECT COMPLETION.</div><div>15. GC IS RESPONSIBLE FOR FINAL PATCHING, PAINT TOUCH-UP, AND CLEANING TO LEAVE ALL WORK, INCLUDING WORK PERFORMED UNDER SEPARATE CONTRACTS, CLEAN AND READY FOR OCCUPANCY.</div><div>16. EXISTING EQUIPMENT AND MATERIALS TO BE REMOVED, WHICH ARE NOT REQUIRED TO BE RELOCATED OR RETAINED BY THE OWNER AND/OR THE DESIGNATED REPRESENTATIVE, SHALL BECOME THE PROPERTY OF THE CONTRACTOR AND BE REMOVED FROM THE PREMISES.</div><div>17. INDICATIONS OF WORK TO BE REMOVED ARE GENERAL ONLY, AND ARE NOT INTENDED TO SHOW ALL ITEMS WHICH MAY REQUIRE REMOVAL. SUCH ITEMS SHALL BE REMOVED, RELOCATED, AND/OR REINSTALLED, AS REQUIRED FOR INSTALLATION OF NEW WORK.</div><div>18. THESE DOCUMENTS DO NOT AUTHORIZE DETERMINING THE PRESENCE, NOR THE REMOVAL, OF ASBESTOS OR OTHER HAZARDOUS MATERIALS. IF DURING THE COURSE OF THE PROJECT, ASBESTOS OR OTHER HAZARDOUS MATERIAL CONTAMINATION IS SUSPECTED, THE CONTRACTOR SHALL NOTIFY THE DESIGNATED REPRESENTATIVE WITHIN 24 HOURS. CONTRACTOR SHALL SUSPEND WORK IN THE AFFECTED AREA UNTIL SUCH A TIME THAT SAID AREA IS CERTIFIED CONTAMINATION-FREE. IN THE INTERIM, THE CONTRACTOR SHALL ENDEAVOR TO RESCHEDULE WORK TO AREAS UNAFFECTED BY SUSPECTED CONTAMINATION IN ORDER TO MINIMIZE DELAY TO THE PROJECT SCHEDULE.</div><div>19. DRYWALL CONSTRUCTION:<div><div>A. PROVIDE SIZES AND TYPES AS SHOWN ON THE DRAWINGS, TAPED AND SPACKLED WITH THREE (3) COATS AND SANDED SMOOTH.</div><div>B. METAL STUDS SHALL BE MINIMUM 20 GA (33 MILS)., UNLESS OTHERWISE NOTED. FASTEN AT 24" O.C. MAXIMUM UTILIZING FASTENERS SUITABLE FOR THE SUBSTRATE.</div><div>C. PROVIDE ALL METAL CORNER BEADS, STOPS, EDGE TRIM, CASINGS, BEADS, ETC. AS REQUIRED TO FINISH ALL DRYWALL SURFACES WITH FLUSH, LEVEL EDGES.</div><div>D. USE FIRE CODE "X" GYPSUM BOARD WHERE REQUIRED TO OBTAIN FIRE RATINGS PER APPLICABLE BUILDING CODES.</div><div>E. UTILIZING MOISTURE RESISTANT GYPSUM BOARD AT ALL "WET" AREAS.</div></div></div><div>20. SEE REFLECTED CEILING PLANS FOR CEILING REQUIREMENTS.</div><div>21. SEE DOOR SCHEDULE FOR DOOR AND FRAME REQUIREMENTS.</div><div>22. PAINT FOR DRYWALL, CONCRETE, AND MASONRY SHALL BE TWO (2) COATS OF BENJAMIN MOORE "EXOSPEC" EGGSHELL LATEX PAINT OVER ONE (1) COAT OF A COMPATIBLE BENJAMIN MOORE QUICK DRY PRIME-SEAL LATEX PRIMER. PAINT FOR MISCELLANEOUS METALS AND TRIM SHALL BE TWO (2) COATS OF BENJAMIN MOORE ODORLESS INTERIOR SEMI-GLOSS "ECOSPEC" PAINT OVER ONE (1) COAT OF A COMPATIBLE BENJAMIN MOORE RUST-INHIBITIVE PRIMER.</div><div>23. CERAMIC FLOOR AND WALL TILE SHALL BE INSTALLED IN STRICT ACCORDANCE WITH THE APPLICABLE PROVISIONS OF THE TILE COUNCIL OF NORTH AMERICA HANDBOOK.</div><div>24. FLAME SPREAD OF ALL INTERIOR FINISHES SHALL MEET OR EXCEED CLASS "B" (ASTM-E-84) (26 TO 75 FLAME SPREAD AND SMOKE DENSITY OF 450 MAX, PER IBC TABLE 803.9).</div><div>25. PROVIDE DRY CHEMICAL "A-B-C" OR TYPE APPROPRIATE FOR THE HAZARD TYPE ENCOUNTERED, 10 lb. CAPACITY FIRE EXTINGUISHERS (F.E.), WHERE INDICATED ON THE FLOOR PLANS AND/OR AS DIRECTED BY THE AUTHORITY HAVING JURISDICTION.</div><div>26. ALL PLUMBING, MECHANICAL, AND ELECTRICAL WORK SHALL BE IN FULL CONFORMANCE WITH THE APPLICABLE EDITIONS OF THE PLUMBING CODE, MECHANICAL CODE AND BUILDING CODE (RESPECTIVELY), AND ALL OTHER APPLICABLE CODES AND REGULATIONS.</div><div>27. PLUMBING WORK SHALL BE INSTALLED BY A PLUMBER LICENSED WITH THE AUTHORITY HAVING JURISDICTION IN ACCORDANCE WITH THE APPLICABLE PLUMBING CODE AND NATIONAL PLUMBING CODES. GC TO COORDINATE SLAB AND WALL DEMOLITION, AND PATCHBACK NECESSARY FOR PLUMBING WORK.</div><div>28. ELECTRICAL WORK SHALL BE INSTALLED BY AN ELECTRICIAN LICENSED WITH THE AUTHORITY HAVING JURISDICTION IN ACCORDANCE WITH THE APPLICABLE BUILDING CODE AND NATIONAL ELECTRICAL CODES. AN ELECTRICAL INSPECTION CERTIFICATE SHALL BE OBTAINED FROM AN INSPECTION AGENCY RECOGNIZED BY THE AUTHORITY HAVING JURISDICTION FOR ALL ELECTRICAL WORK, AND SUPPLIED TO THE DESIGNATED REPRESENTATIVE.</div><div>29. ALL WOOD FRAMING, BLOCKING, ETC, SHALL BE FIRE TREATED.</div><div>30. ALL WOOD FRAMING, BLOCKING, ETC, IN CONTACT WITH CONCRETE SHALL BE PRESSURE TREATED AND SET IN MASTIC.</div><div>31. PROVIDE ANY AND ALL FIRE RETARDANT TREATED WOOD BLOCKING/BACKING OR 14 GA. GALV. FLAT STOCK BACKING AS REQUIRED TO ENSURE PROPER AND ADEQUATE SUPPORT (IN COMPLIANCE WITH BUILDING CODE MINIMUM LOADING REQUIREMENTS WHERE APPLICABLE) OF VARIOUS ITEMS INCLUDING, BUT NOT NECESSARILY LIMITED TO, HANDRAILS, CABINETRY, SHELVING, HANDICAP GRAB BARS, TOILET ACCESSORIES, CABLE TRAYS, CONDUITS, ETC.</div><div>32. ALL HANDICAP ACCESSIBILITY WORK SHALL BE PERFORMED IN STRICT ACCORDANCE WITH 2010 ADA, ICC ANSI A117.1-2009, AND BUILDING CODE HANDICAP ACCESSIBILITY GUIDELINES AND REFERENCE STANDARDS.</div><div>33. GENERAL CONTRACTOR AND EACH SUB-CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING ALL REQUIREMENTS AND ITEMS OF WORK THAT MAY BE REQUIRED TO PROVIDE FOR AND/OR ACCOMMODATE WORK OF OTHER TRADES INCLUDING WORK OF DESIGNATED REPRESENTATIVE SELECTED SECURITY VENDORS, COMMUNICATION VENDORS, AND OTHER VENDORS AS MAY BE ENGAGED. NO EXTRA WILL BE ENTERTAINED DUE TO THE LACK OF SUCH COORDINATION.</div><div>34. CONTRACTOR SHALL SUBMIT TO DESIGNATED REPRESENTATIVE ALL CUTS, M.S.D.S. SHEETS, AND SAMPLES OF FINISHES, EQUIPMENT &amp; MATERIALS FOR APPROVAL PRIOR TO ORDERING, FABRICATION, OR COMMENCEMENT OF THE WORK. ALL SUBMISSIONS SHALL BE PROVIDED IN SETS OF FIVE (5) AND TIMED SUCH THAT MATERIAL DELIVERIES &amp; INSTALLATION ACCOMMODATE THE SCHEDULE &amp; COMPLETION DATE ESTABLISHED BY THE DESIGNATED REPRESENTATIVE.</div><div>35. FOR PORTIONS OF THE BUILDING THAT REMAIN OCCUPIED DURING CONSTRUCTION, CONTRACTOR SHALL PROVIDE ALL REQUIRED TEMPORARY PARTITIONS, DUST PROTECTION AND SEPARATION REQUIRED TO PROVIDE OCCUPANTS WITH SAFE EGRESS, AND ACCESS TO REQUIRED FACILITIES (I.E. RESTROOMS, ELEC. CLOSETS, ETC.) CONTRACTOR SHALL MINIMIZE DISRUPTION TO OCCUPANTS AS A RESULT OF NOISE, TRAFFIC, PARKING, SITE AND BUILDING ACCESS, ETC.</div><div>36. CONTRACTOR SHALL PROVIDE A MINIMUM OF 72 HOURS WRITTEN NOTICE TO DESIGNATED REPRESENTATIVES FOR ANY PLANNED DISRUPTIONS OF BUILDING PLUMBING, MECHANICAL, ELECTRICAL, OR OTHER CRITICAL SYSTEMS SERVICING THE TENANT SPACE.</div><div>37. ALL INTENSIVE NOISE PRODUCING ACTIVITIES SUCH AS CORE DRILLING, CONCRETE SLAB CUTTING OR CHOPPING MAY BE PERFORMED OFF HOURS. COORDINATE REQUIREMENTS WITH DESIGNATED REPRESENTATIVES AND INCORPORATE INTO BASE BID.</div><div>38. IT IS NOT THE INTENT TO SHOW EACH AND EVERY PART OR COMPONENT OF ANY GIVEN ASSEMBLY, BUT RATHER TO SHOW SYSTEMS IN PLACE DEPICTING THE DESIRED END PRODUCT. CONTRACTOR SHALL PROVIDE ANY AND ALL PERIPHERAL ITEMS THAT MAY REASONABLY BE UNDERSTOOD AS BEING NECESSARY FOR THE COMPLETE AND PROPER EXECUTION OF THE WORK. THE COST FOR THESE ITEMS SHALL BE INCORPORATED INTO THE CONTRACTORS BASE BID. NO EXTRA WILL BE ENTERTAINED DUE TO LACK OF INCLUSION IN THE WORK.</div><div>39. THE DESIGNATED REPRESENTATIVE, THE ARCHITECT AND/OR THEIR CONSULTANTS DO NOT IMPLY, NOR DO THEY ASSUME RESPONSIBILITY FOR, THE METHOD OF DEMOLITION AND CONSTRUCTION. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SHORING, BRACING, AND PROTECTION OF EXISTING AND NEW WORK, AS MAY BE REQUIRED FOR PROTECTING THE INTEGRITY OF THE STRUCTURE, AND FOR ENSURING THE SAFETY OF ITS OCCUPANTS.</div><div>40. REFER TO DECOR COMPANY DRAWINGS FOR FINISH PRODUCT SPECIFICATIONS. (SEE NOTE 24 FOR ADDITIONAL REQUIREMENTS). G.C. TO COORDINATE ORDERING OF PRODUCTS WITH DECOR VENDOR.</div><div>41. REFER TO DECOR COMPANY DRAWINGS FOR SEATING LAYOUT, ADDITIONAL FRONT COUNTER INFORMATION, CEILING HEIGHTS, AND FINISHES.</div><div>42. AT PRE-CON MEETING, GC TO VERIFY POWER AND DATA REQUIREMENTS FOR CREW ROOM.</div><div>43. DECORATIVE MATERIALS SHALL BE FLAME RETARDANT AND MEET THE CRITERIA OF NFPA 701.</div><div>44. DECORATIVE MATERIAL SHALL NOT CONCEAL EXITS. EXIT LIGHTS, ALARM STATIONS, HOSE CABINETS AND EXTINGUISHER LOCATIONS.</div><div>45. WHEN BUILDING TYPE IS A NON-COMBUSTIBLE CATEGORY, ALL PLYWOOD SHALL BE FIRE RETARDANT TREATED.</div><div>46. A. FRP OVER CEMENT BD BEHIND 3-COMP SINK TO HEIGHT OF BACK SPLASH.<div>B. TILE WAINSCOTT TO 6' A.F.F. OVER CEMENT BD. OVER EXT GRADE PLYWOOD (NOTE 4) AT MOP SINKS.</div></div><div>47. PROVIDE CEMENT BOARD BACKER OR EQUIVALENT AT ALL TILE LOCATIONS.</div><div>48. PROVIDE VAPOR BARRIER BEHIND PLYWOOD AT WALLS AND BEHIND GYP. BD. AT CEILING.</div><div>49. SEE CEILING PLAN FOR HEIGHTS &amp; LAYOUTS.</div><div>50. VWC ON EXTERIOR WALL ASSEMBLIES TO BE PERFORATED.</div></div></div>		
1	SYMBOLS/LEGEND	2	ABBREVIATIONS	3	GENERAL NOTES



